



ASK [EM] Format
Proximity & PIN
Time & Attendance Access Controller

IP505R



IP505R



KEY Features

- 125KHz Standalone Proximity / PIN Access Controller
- ASK [EM] Format
- Dual Function for Access Control and Time & Attendance
- Dynamic Control of Memory up to 50,000 Users / up to 50,000 Event Buffers (Available on VA.1.0 and above)
- Dynamic Control of Memory up to 4,000 Users / up to 26,000 Event Buffers (Available on V8.1.0 and below)
- Standalone / Network Communication via RS232 / RS422 / RS485 (Max.32ch), TCP/IP (External LAN Converter required)
- 1ea of External Reader Port for Anti-passback: 26bit Wiegand and 4 / 8bit Burst for PIN
- Duress Mode Function
- Independent 4 Inputs and 4 Outputs including 2ea of 2 Form-C Relay Outputs
- Dual Tamper Switches
- Alarm Event Monitoring using Tamper Switch (by Application Software)
- Mode Selection: RF only / PIN (4-6digit) only / RF + P/W (4digit)
- Compatible Software: STARWATCH DUAL PRO I/II

Time Schedules

- Time Code : 10
- Time Interval : 5
- Holiday Code : 10
- Holiday : 32

Standalone Configuration

