

DS-K1T671MF Face Recognition Terminal



- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens, Built-in Mifare card reading module
- Face recognition distance (without face mask): 0.3 m to 3 m
- Duration < 0.2 s/User
- Accuracy rate ≥ 99%
- Max. 6000 faces, Max. 6000 cards and Max. 5000 fingerprints
- Two-way audio with client software, indoor station, and main station
- Supports TCP/IP, Wi-Fi
- Configuration via the web client
- Supports ISAPI and EHome 5.0 protocol
- IP65




▪ Specification

Display	
Dimensions	7-inch
Type	LCD
Operation method	Capacitive touch screen
Video	
Pixel	2 MP
Lens	2
Audio	
Tone quality	Noise suppression and echo cancellation
Network	
Wired network	10 M/100 M/1000 M self-adaptive
Interface	
Network interface	1
Lock output	1
Exit button	1
Door contact input	1
Power interface	2-pin
Capacity	
Card capacity	6000
Face capacity	6000
Fingerprint capacity	5000
Event capacity	50,000
Authentication	
Card type	Mifare 1 card
Card reading frequency	13.56MHz
Card reading distance	0 to 5 cm
Face recognition distance	0.3 to 3 m (without face mask)
Function	
QR code recognition	Support
Face anti-spoofing	Support
Audio prompt	Support
Time synchronization	Support
General	
Power supply method	2-pin connector
Power supply	12 VDC/2 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	0~90% (No condensing)
Dimensions	290 mm × 116.5 mm × 33 mm (11.4" × 4.6" × 1.3")
Protective level	IP65
Installation	Surface

▪ Available Model

DS-K1T671MF

▪ Dimension



▪ Accessory

▪ Optional

DS-K3H4410-120	DS-KAB671-S Protective Shield	DS-KAB671-B Stand Stick	DS-K3H4411-120	DS-KAB671-S Protective Shield
DS-KAB671-P1	DS-KAB671-B Stand Stick			